

EASY RELEASE

Speed system separation link



The EASY RELEASE is used to automatically disconnect the speed system when using separation carabiners after reserve parachute deployment. The system convinces by low construction height, weight neutrality compared to a standard Brummel hook connection and durable, safe function.

Scope of delivery

2x Ring clip with speed system line for attachment to the paraglider risers



2x Release hook with speed system line (static line) for attachment to the speed system lines of the paragliding harness



Installation

1. First, check if the Brummel hooks on your speed system lines can be detached. If so, you can attach the ring clips of the EASY RELEASE instead (see pictures).



Detaching the Brummel hook



Attaching the ring clip



2. If the Brummel hooks cannot be detached, remove the original speed system lines with the Brummel hooks on the risers. Depending on the design of your speed system, you may have to cut the lines for this purpose. Then, install the ring clips of the EASY RELEASE with the speed system lines instead of the original lines with Brummel hooks.

3. Adjust the line lengths so that the ring clips sit as close as possible to the upper pulleys. Never adjust them so short that the lines are under tension and cause pre-acceleration during flight. If the lines are set too long, it may not be possible to use the full possible length of the speed system, as the separation link may then be stopped at the passage to the harness. Now, attach the lines with bowline knots and simple securing knots at the free ends, tighten firmly and check

the position of the ring clips again. If necessary, cut the free, protruding line ends to approx. 2 cm.

4. Attach the release lines of the EASY RELEASE on the harness. Then, install the speed system lines according to your harness manufacturer's instruction manual and adjust the speed system line lengths.

5. Snap the release hooks into the ring clips. The EASY RELEASE separation link is now ready for use! When the separation carabiner is opened, the release lines turn the hook in the pulling direction of the detached risers and the ring clips release automatically.

